



Docket No.: 245677US0X

COMMISSIONER FOR PATENTS
ALEXANDRIA, VIRGINIA 22313



RE: Application Serial No.: 10/716,460
Applicants: Daniele BIANCHI, et al.
Filing Date: November 20, 2003
For: INTEGRATED PROCESS FOR THE PREPARATION
OF PHENOL FROM BENZENE WITH RECYCLING
OF THE BY-PRODUCTS
Group Art Unit: 1621
Examiner: SHIPPEN, Michael L.

SIR:

Attached hereto for filing are the following papers:

Letter

**English translation of Italian Patent Application No. MI 2002-A-002522 w/
Translator's Statement (Executed)**

Our check in the amount of \$0.00 is attached covering any required fees. In the event any variance exists between the amount enclosed and the Patent Office charges for filing the above-noted documents, including any fees required under 37 C.F.R. 1.136 for any necessary Extension of Time to make the filing of the attached documents timely, please charge or credit the difference to our Deposit Account No. 15-0030. Further, if these papers are not considered timely filed, then a petition is hereby made under 37 C.F.R. 1.136 for the necessary extension of time. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.

Norman F. Oblon

Daniel R. Evans, Ph.D.
Registration No. 55,868

Customer Number

22850

(703) 413-3000 (phone)
(703) 413-2220 (fax)

DOCKET NO: 245677US0X



IN THE UNITED STATES PATENT & TRADEMARK OFFICE

IN RE APPLICATION OF :

DANIELE BIANCHI, ET AL. :

EXAMINER: SHIPPEN, MICHAEL L.

SERIAL NO: 10/716,460 :

FILED: NOVEMBER 20, 2003 :

GROUP ART UNIT: 1621

FOR: INTEGRATED PROCESS FOR THE :
PREPARATION OF PHENOL FROM
BENZENE WITH RECYCLING OF THE
BY-PRODUCTS

LETTER

COMMISSIONER FOR PATENTS
ALEXANDRIA, VIRGINIA 22313

SIR:

Further to the Amendment and Request for Reconsideration filed September 21, 2005, Applicants file concurrently herewith an English translation of the priority application of the present application, Italian Patent Application No. MI 2002-A-002522 (MI '522), which was filed in the Italian Patent and Trademark Office on November 28, 2002. Attached to the English translation of MI '522 is a statement by the translator, Antonella De Gregori, which states that the English translation of MI '522 is believed to be a true translation of MI '522.


Respectfully submitted,


OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.
Norman F. Oblon

Customer Number

22850

Tel: (703) 413-3000
Fax: (703) 413 -2220
(OSMMN 06/04)


Daniel R. Evans, Ph.D.
Registration No. 55,868



TO THE MINISTRY OF THE PRODUCTIVE INDUSTRIES
Italian Patent and Trademark Office - ROME
APPLICATION FOR PATENT FOR INDUSTRIAL INVENTION, POSTPONED
FILING OF DOCUMENTS, ANTICIPATED LAYING-OPEN TO PUBLIC
INSPECTION

FORM A
Stamp

A. APPLICANT(S) :

1) Name POLIMERI EUROPA S.p.A.
Head Office/Residence BRINDISI - Via E. Fermi 4 Code
2) Name
Head Office/Residence Code

B. APPLICANT REPRESENTATIVE C/O I.P.T.O.

Surname, Name CAVALIERE Giambattista et al Fiscal Code 07562850151
Style of the Office ENITECNOLOGIE S.p.A. -BREVETTI E LICENZE
Street .F.Maritano no.26 City S.DONATO MIL. ZIP 20097 Prov. MI
C.ELECTED DOMICILE ADDRESSEE see above
Street no. City ZIP Province

D.TITLE Proposed Classification C07C group/subgroup

"INTEGRATED PROCESS FOR THE PREPARATION OF PHENOL FROM BENZENE
WITH RECYCLING OF THE BY-PRODUCTS"

ANTICIPATED LAYING-OPEN TO THE PUBLIC: Y/N **PETITION:** Date **RECORD No.**

E. DESIGNATED INVENTORS:

Surname, Name	Surname, Name
1) BIANCHI Daniele	3) BUZZONI Roberto
2) BORTOLO Rossella	4) CESANA Alberto

F. PRIORITY:

State	Type	Appln no.	Filing date	Encl.Y/Res.	CANCELLATION OF POSTPONED FILING DATE RECORD No.
-------	------	-----------	-------------	-------------	-----------------------------------------------------

1) NONE
2)

G. COLLECTING CENTRE OF MICROORGANISM COLTURES, Style

H. SPECIAL NOTES:

DOCUMENTS ENCLOSED:

CANCELLATION OF POSTPONED
FILING DATE RECORD no.
TO BE COMPARED WITH EACH PRIORITY

Doc.1) 2 PROV. no. 38 pages	abstract with drawing, description and claims (1 copy compulsory)
Doc.2) 2 PROV. no. 01 table	drawing (1 copy compulsory if mentioned in the description)
Doc.3) 1 TO FOLLOW	Ref. to General Power of Attorney
Doc.4) 1 TO FOLLOW	Inventor's Designation
Doc.5) 0 TO FOLLOW	Priority Docs. with Italian translation
Doc.6) 0 TO FOLLOW	Authorisation or Assignment Deed
Doc.7) 0 TO FOLLOW	Full Applicant's name
8) Certification of payment for Euro 291.80.= compulsory	

FILLED IN ON 27/11/2002

Signature of Applicant(s) THE AGENT Eng. Giambattista CAVALIERE

TO BE CONTINUED YES/XX

CERTIFIED COPY HEREOF IS REQUESTED YES/XX
CHAMBER OF COMMERCE, INDUSTRY, HANDICRAFT, AGRICULTURE OF MILANO
Code:15

FILING CERTIFICATE. APPLICATION NUMBER MI2002A 002522 Reg.A
In the year TWO THOUSAND AND TWO on the 28th day of the month
of NOVEMBER

The above mentioned Applicant(s) has (have) filed before me the
undersigned the present application consisting of no. 01
additional sheets for the grant of the patent aforementioned.

I. VARIOUS NOTES BY THE ATTESTING OFFICER:

For the Applicant	signature	ATTESTING OFFICER	signature
	seal		
	of the Office		

ADDITIONAL SHEET TO FORM A

ADDITIONAL SHEET n. 01 of 01 APPLICATION N. MI2002A 002522 REG.A

A. APPLICANT(S)

Name		
Residence		Code
Name		
Residence		Code
Name		
Residence		Code
Name		
Residence		Code

E. DESIGNATED INVENTORS

Surname	name	surname	name
05	DALLORO	Leonardo	
06	D'ALOSIO	Rino	

F. PRIORITY

State	Type	No.	Filing date	Encl.Y/Res.
-------	------	-----	-------------	-------------

CANCELLATION OF RESERVE
Date. Rec.No.

SIGNATURE OF APPLICANT(S) THE AGENT Eng. Giambattista CAVALIERE

SPACE TO BE FILLED IN BY THE ITALIAN PATENT AND TRADEMARK OFFICE

ABSTRACT OF THE INVENTION WITH MAIN DRAWING, DESCRIPTION AND CLAIM

APPLICATION NUMBER MI2002A 002522 REG.A
PATENT NUMBER

FILING DATE 28/11/2002
ISSUE DATE

D. TITLE

"INTEGRATED PROCESS FOR THE PREPARATION OF PHENOL FROM BENZENE WITH RECYCLING OF THE BY-PRODUCTS"

L. ABSTRACT

The invention relates to a process for the preparation of phenol comprising the following phases:

- 1) preparation in continuous of phenol by means of the direct oxidation of benzene with hydrogen peroxide operating with an H_2O_2 /benzene ratio ranging from 10 to 70%, in a three-phase reaction system comprising a first liquid phase consisting of benzene and an organic solvent, a second liquid phase consisting of water, a solid phase consisting of an activated catalyst based on titanium silicalite TS-1;
- 2) separation of the phenol and non-reacted benzene from the reaction mixture of the oxidation section (1), by means of fractionated distillation;
- 3) separation of the solvent and by-products from the mixture coming from the distillation tail (2), by means of basic extraction;
- 4) transformation of the by-products obtain in section (3) to phenol by means of hydrodeoxygenation with hydrogen operating in continuous, in aqueous solution, at a temperature ranging from 250 to 500°C, at pressures of 1-100 bar and in the presence of a catalyst based on elements of group VIB or their mixtures or group VIII of the periodic table or their mixtures;
- 5) recycling of the phenol obtained in section (4) to the distillation section (2).

M. DRAWING

Fig. 1

INTEGRATED PROCESS FOR THE PREPARATION OF PHENOL FROM BEN-
ZENE WITH RECYCLING OF THE BY-PRODUCTS

POLIMERI EUROPA S.p.A.

5 Via Enrico Fermi 4 - Brindisi

DESCRIPTION

The present invention relates to an integrated process
for the synthesis of phenol from benzene by the direct oxi-
10 dation of benzene with hydrogen peroxide, in the presence
of a zeolitic catalyst TS-1 and recycling of the by-
products.

More specifically, the invention relates to a process
for the preparation of phenol wherein the reaction by-
15 products are selectively transformed into phenol and recy-
cled in the process streams.

Phenol is an extremely important industrial intermedi-
ate used, for example, in the production of polycarbonates
or other phenolic resins.

20 Phenol is currently produced industrially starting
from cumene. Various processes for the preparation of phe-
nol, however, comprising the direct oxidation of benzene
with hydrogen peroxide, in the presence of appropriate
catalytic systems, are known in the art.

25

These processes are generally carried out in an organic solvent capable of improving the contact between the organic substrate and hydrogen peroxide such as, for example, methanol, ethanol or isopropyl alcohol. Ketones such as acetone, methylethylketone, or acetic acid or acetonitrile, as described in U.S. patents 4,396,783, GB 2,116,974, are also suitable for the purpose.

European patent application EP A 919531 describes the use of a specific solvent such as sulfolane for obtaining significant improvements in the conversion and selectivity of these processes (EP A 919531). Alternatively, improvements in conversion and selectivity can also be obtained by activation of the catalyst with hydrogen peroxide and fluorine ions, as described in European patent application EP A 958861.

The processes for the preparation of phenol by the direct oxidation of benzene with hydrogen peroxide are generally carried out in a biphasic reaction system (solid catalyst/organic phase), in the presence of suitable catalytic systems.

Italian patent application MI 2001A 002410 describes a process which operates in a three-phase reaction system consisting of a solid catalyst/aqueous phase/organic phase (aromatic compound + solvent) which, with respect to the biphasic system, allows the productivity of the oxidation

process of benzene to be increased without jeopardizing the selectivity.

High productivities, however, are not even reached by operating in a three-phase system. This is due to the fact
5 that the process must be carried out at low conversions of benzene to limit the consecutive oxidation reactions of phenol to by-products (catechol and hydroquinone). For example, the above-mentioned patent application MI 2001 A 002410 specifies that with a benzene conversion of 12.2%
10 and a selectivity to phenol of 90%, 111 kg of hydroquinone and catechol (in a 55/45 mixture) are co-produced, for each ton of phenol. The quantity of these by-products is such that they cannot be absorbed by the market and must therefore be disposed of, further increasing the process costs.
15 Furthermore, again as a result of the low productivity, it is necessary to separate and recycle 20.1 kg of solvents (sulfolane, benzene and water) for each Kg of phenol produced. The high volume of recycled products causes an overdimensioning of the recovery section of the industrial
20 plant.

It has now been found that the drawbacks described above can be reduced when operating according to the process of the present invention.

In practice, the process of the invention envisages
25 integration of the synthesis process of phenol with a hy-

drodeoxygenation section of the by-products, hydroquinone and catechol, which are selectively transformed into phenol and recycled in the process streams and the running of the synthesis section of phenol under particular operating conditions.

By operating according to the process of the invention, the following advantages are obtained:

- elimination of the co-production of biphenols (the final selectivity to phenol, after recovery of the by-products, proves to be equal to 99%)
- saving in the disposal costs;
- increase in the process productivity, which can be pushed to 159 g of phenol/litre of reaction mixture (as per example 8 of the present patent), with a consequent reduction in the quantity of solvents to be recycled (5.3 kg per kg of phenol) and plant investment costs (relating to the recovery section).

In accordance with this, the object of the present invention relates to a process for the preparation of phenol comprising the following phases:

- 1) preparation in continuous of phenol by means of the direct oxidation of benzene with hydrogen peroxide operating with an H_2O_2 /benzene ratio ranging from 10 to 70%, in a three-phase reaction system comprising a first liquid phase consisting of benzene and an organic solvent, a second liq-

uid phase consisting of water, a solid phase consisting of an activated catalyst based on titanium silicalite TS-1;

2) separation of the phenol and non-reacted benzene from the reaction mixture of the oxidation section (1), by means of fractionated distillation;

3) separation of the solvent and by-products from the mixture coming from the distillation tail (2), by means of basic extraction;

4) transformation of the by-products obtained in section (3) to phenol by means of hydrodeoxygenation with hydrogen operating in continuous, in aqueous solution, at a temperature ranging from 250 to 500°C, at pressures of 1-100 bar and in the presence of a catalyst based on elements of group VIB or their mixtures or group VIII of the periodic table or their mixtures;

5) recycling of the phenol obtained in section (4) to the distillation section (2).

The integration between the oxidation process of benzene to phenol and the hydrodeoxygenation of the by-products to phenol is particularly advantageous also because (as described in Italian patent application MI 2002A 001187), it is possible to obtain biphenols, leaving the recovery section of the by-products, in the form of an aqueous solution which can be used directly in the hydrodeoxygenation section without evaporation of the solvent.

Furthermore, the integration of the two processes allows an H_2O_2 /benzene molar ratio to be adopted within a wider range with respect to the process described in Italian Patent Application MI 2001 A 002410, thus enabling high conversions to benzene and a high productivity to be reached.

Under these conditions, there is a greater formation of by-products which however are converted to phenol in the hydrodeoxygenation section.

The preparation of phenol by the direct oxidation of benzene (Figure 1, section a) is carried out in a reactor into which benzene, the solvent, water, the catalyst and hydrogen peroxide are fed and where an organic phase is obtained, containing the solvent, non-reacted benzene, water, phenol and by-products (catechol, hydroquinone and phenolic tars).

The three-phase reaction system is reached when operating with a controlled quantity of water which is such as to cause a demixing of the liquid phase and prevent the aggregation of the catalyst.

The oxidation reaction of benzene is conveniently carried out with a concentration of water ranging from 5 to 50% by weight, concentrations ranging from 15 to 40% are preferably used.

The organic solvent can be selected from solvents

These substituted titanium silicalites and the methods for their preparation are described in European patent applications 226,257, 226,258 and 266,825.

The catalyst is generally used in quantities ranging
5 from 2 to 60% by weight with respect to the aromatic substrate.

Quantities of catalyst ranging from 5 to 40% by weight with respect to the aromatic substrate are preferably used.

The hydrogen peroxide is added to the reaction mixture
10 in quantities ranging from 10 to 70% in moles with respect to the aromatic substrate, preferably between 20 and 60% in moles.

Solutions of hydrogen peroxide are conveniently used at a concentration ranging from 10 to 60% by weight, preferably
15 erably from 15 to 60% by weight.

The benzene is normally used in quantities ranging from 10 to 80% by weight with respect to the reaction mixture.

Quantities of benzene ranging from 15 to 50% by weight
20 with respect to the reaction mixture are preferably used.

The oxidation reaction is carried out at temperatures ranging from 50° to 110°C, preferably from 70° to 100°C.

The reaction time necessary for the complete use of the hydrogen peroxide depends on the reaction conditions
25 used.

The oxidation process described in the present invention can be carried out in reactors of the semibatch type (with the feeding of hydrogen peroxide) or of the CSTR type (continuous stirred batch reactor) with feeding in continuous of the hydrogen peroxide and benzene/solvent mixture.

Operating in a continuous process, the aqueous phase (in which the catalyst is selectively distributed), is maintained inside the reactor removing the organic phase in a quiet, unstirred zone in which the demixing is effected. In this way, only one phase containing: an aromatic compound, a solvent, a hydroxy-aromatic compound and by-products, is obtained at the outlet.

By operating under the process conditions of the invention, it is also possible to operate at 100°C obtaining an increase in the catalytic activity without a loss in selectivity, as normally happened when operating in double phase.

The separation and recovery of the light components of the reaction mixture coming from the oxidation section is carried out by means of fractionated distillation.

The azeotropic mixture of benzene/water is obtained at the head in a first column (Figure 1, section b) together with a mixture of solvent, phenol and by-products (catechols, hydroquinone, phenolic tars) at the tail. This mixture is sent to a second distillation column (Figure 1,

section c) where purified phenol is obtained at the head and a mixture of solvent and by-products at the tail.

The by-products (catechol, hydroquinone and phenolic tars) are separated from the reaction solvent (preferably sulfolane) by means of the procedure described in Italian patent application MI 2002A 001187, which comprises the following phases:

- a mixing and separation section (Figure 1, section d) fed with the bottom stream of the phenol distillation unit (Figure 1, section c), consisting of sulfolane and by-products, the benzene stream, coming from the head of the benzene distillation section (Figure 1, section b) and a basic aqueous solution. An organic phase containing sulfolane, benzene and water (recycled to the section) and an aqueous phase, containing catechol salts, hydroquinone and tars, are obtained at the outlet;
- a mixing section (Figure 1, section e), for the acidification of the aqueous phase coming from section (d) with an inorganic acid or CO₂ to release the catechol, hydroquinone and tars from their salts;
- a separation section (Figure 1, section f) fed with the stream coming from section (e) containing water, salts, catechol, hydroquinone and tars, and with an extraction solvent (preferably methylisobutylketone);

a distillation unit section (Figure 1, section g) for the separation at the head of the extraction solvent which is recycled to section (f) and an aqueous solution of catechol, hydroquinone and tars, at the tail.

5 The by-products obtained from the recovery section (Figure 1, section g) are then transformed into phenol by means of hydrodeoxygenation with hydrogen (Figure 1, section h).

The reaction is carried out in vapour phase at a temperature of 250-500°C, preferably 300-450°C, at a pressure of 1-100 bar, preferably 3-50 bar, and at a space velocity (WHSV = Weight Hourly Space Velocity, expressed in kg of Benzenediols/h/kg of catalyst) of 0.1-10 h⁻¹, preferably 0.5-5 h⁻¹.

15 In particular, the feeding of the reactor consists of a solution of benzenediols in water at a concentration of 5-60% by weight, preferably 10-40% by weight, and hydrogen with a molar ratio with respect to the benzenediols of 2-50, preferably 5-30.

20 The catalyst can be selected from those for hydrodeoxygenation based on elements of group VIB or group VIII of the periodic table.

When the catalyst is based on elements of group VIB, it can contain, as promoters, elements belonging to group VIII and phosphorous. The elements of group VIB can be used

25

in a mixture and, among these, molybdenum and tungsten are preferred. Among the promoters of group VIII, nickel, cobalt, iron and ruthenium are preferred; they can be used in a mixture with each other and with phosphorous.

5 When the catalyst is based on elements of group VIII, it can contain, as promoters, zinc, rhenium, selenium, tin, germanium and lead. The elements of group VIII can be used in a mixture and, among these, cobalt, palladium, nickel and platinum are preferred. The promoters can also be used
10 in a mixture with each other.

The active phase is preferably deposited on a carrier.

Preferred carriers are inorganic oxides such as alumina, silica, titanium dioxide, crystalline or amorphous alumino-silicates, crystalline spinels having the general
15 formula $F^{2+}R_2^{3+}O_4$ (wherein F^{2+} can be Mg, Fe, Zn, Mn, Ni, etc. and R^{3+} can be Al, Fe, Cr, etc.) or their mixtures.

For catalysts based on an element of group VIB, said element is generally present on the carrier in a concentration ranging from 1 to 50% by weight, preferably from 3-30%
20 by weight. The promoters of these catalysts are generally present in concentrations ranging from 0.1 to 100% atomic with respect to the element of group VIB, preferably from 1 to 50%. Without limiting the possible compositions in any way, or indicating preferences, examples of these catalysts
25 are Mo, W, CoMo, NiMo, NiW, FeMo, RuMo, CoMoP, NiMoP,

CoWMO, CoWMO_P.

Before being used in the reaction, these catalysts can be subjected to treatment to modify their chemical characteristics, for example sulfuration with H₂S, dimethylsulfide, dimethyldisulfide, carbon sulfide or any other compound useful for the purpose.

For catalysts based on an element of group VIII, said element is generally present on the carrier in a concentration ranging from 0.05 to 20% by weight, preferably from 0.1 to 10% by weight. The promoters of these catalysts are generally present in concentrations ranging from 0.5 to 200% atomic with respect to the element of group VIII, preferably from 1 to 120%. Without limiting the possible compositions in any way, or indicating preferences, examples of these catalysts are Pt, Pd, Co, Ni, PtZn, PtRe, PtNi, PtSe, PtSn, PtGe, PtPb, PdPb, PdSn.

With the most appropriate catalysts and operating conditions, it is possible to keep the reactor operating for times prolonged for several hundreds of hours, with a conversion of benzenediols of 100% and a selectivity to phenol >95%.

By prolonging the running of the reactor, the conversion tends to be reduced, whereas the selectivity still remains extremely high. In order to maintain the desired conversion degree, the reaction temperature can be progres-

sively increased within the range of 250-500°C.

It has been verified that the catalysts which can be used for the purposes of the invention can be subjected without any particular problems to periodical regeneration, according to what is known in the state of the art, in order to recover the initial activity.

In particular, the overall process comprises the following sections:

- a) oxidation unit, containing the catalyst and fed with benzene, sulfolane, water and hydrogen peroxide;
- b) distillation unit for the separation at the head of the water/benzene azeotropic mixture;
- c) distillation unit for the separation at the head of the phenol;
- d) mixing and separation unit fed with the bottom stream of the distillation unit (c), consisting of sulfolane, biphenols and phenolic tars, the benzene flow, coming from section (b) and a basic aqueous solution. An organic phase is obtained at the outlet, containing sulfolane, benzene and water (recycled to section a) and an aqueous phase, containing salts of biphenols and tars;
- e) mixing unit for the acidification of the aqueous phase coming from section (d) with an inorganic acid or CO₂ to release the biphenols and tars from their salts;
- f) separation unit fed with the stream coming from section

(e) containing water, salts, biphenols and tars, and with an extraction solvent (for example methylisobutylketone).

g) distillation unit for the separation at the head of the extraction solvent which is recycled to section (f);

5 h) hydrodeoxygenation unit containing the catalyst, fed with the stream at the tail of section (g), consisting of biphenols, tars and water, and with hydrogen. The outgoing stream, containing the recovered phenol and water is recycled to section (c).

10 The simplified integrated process scheme is provided in Figure 1.

The following examples have the sole purpose of describing the present invention in greater detail and should in no way be considered as limiting its scope.

15 EXAMPLE 1

Activation of the catalyst

3.0 g (1.43 mmoles of Ti) of TS-1 catalyst (EniChem, Ti = 2.29% by weight) and 0.11 g of NH_4HF_2 (average titer 92.5%) in 35 ml of water, corresponding to a molar ratio
20 F/Ti = 2.5, are charged into a 100 ml glass flask, equipped with a mechanical stirrer, reflux condenser, thermometer and oil circulation thermostat. The aqueous suspension of the catalyst, maintained under mechanical stirring, is heated to 60°C. 1.6 ml of H_2O_2 at 30% by weight, equal to a
25 molar ratio $\text{H}_2\text{O}_2/\text{Ti}$ = 11, are subsequently added and the

suspension is maintained under stirring at 60°C for 4 hours. After cooling, the solid is separated from the mother liquor (pH 4.3) by filtration on a porous septum, then repeatedly washed with deionized water and finally
5 with acetone. The catalyst is subsequently dried under vacuum at 40°C for 8 hours and then subjected, with a heating rate of 50°C/h, to thermal treatment in air at 550°C for 4 hours. Titer of the activated catalyst = 1.49% of Ti. The dissolved titanium corresponds to 35% by weight.

10 EXAMPLE 2

Three-phase system under semi-batch conditions (comparative example MI2001A 002410)

An AISI 316 reactor (volume = 600 ml) is pressurized with nitrogen to a pressure of 5 atm. 100 g of benzene
15 (1.28 moles), 180 g of sulfolane, 43 g of water and 10 g of catalyst activated as specified in Example 1 (equal to 3.1 mmoles of Ti) are then charged. The liquid fraction of the reaction mixture is in this case three-phase. The temperature of the reactor is brought to 100°C.

20 21.75 g (192 mmoles of H_2O_2 ; $\text{H}_2\text{O}_2/\text{benzene} = 0.15$) of an aqueous solution of H_2O_2 at 30% w/w are subsequently added over a period of 1 hour.

The reaction mixture is then cooled to 20°C and the catalyst is separated by filtration on a porous septum.

25 At the end of the reaction two phases are separated,

with the following composition:

upper organic phase (85% by weight):

benzene/sulfolane/water 1/3/96 by weight

lower aqueous phase (15% by weight):

5 benzene/sulfolane/water 61/38/1 by weight.

The organic phase is analyzed by means of HPLC revealing the formation of the following products:

phenol 13.3 g (141.1 mmoles)

hydroquinone 0.69 g (6.3 mmoles)

10 catechol 1.03 g (9.4 mmoles).

The reaction mixture was then evaporated at reduced pressure obtaining only traces of polyphenolic tars as boiler residue.

The reaction performances are consequently the following:
15 ing:

- benzene conversion (C1) = 12.2% (in moles);
- H₂O₂ conversion (C2) = 98% (in moles);
- selectivity to phenol (S1) = 90% (in moles);
- selectivity on H₂O₂ (S2) = 75% (in moles);
- 20 - concentration of phenol in the final reaction mixture (organic phase) = 4.75% (by weight).

Operating under these conditions, during the recovery and purification phase of the reaction products, it is necessary to evaporate 20.1 Kg of solvent (sulfolane and
25 non-reacted benzene) per Kg of phenol.

The co-production of by-products is equal to 52.0 kg hydroquinone/kg phenol and 78.0 kg catechol/ton phenol.

EXAMPLE 3

An AISI 316 reactor (volume = 600 ml) is pressurized with nitrogen to a pressure of 5 atm. 100 g of benzene (1.28 moles), 296 g of sulfolane, 169 g of water and 10 g of catalyst activated as specified in Example 1 (equal to 3.1 mmoles of Ti) are then charged. The liquid fraction of the reaction mixture is in this case three-phase. The temperature of the reactor is brought to 100°C.

29.1 g (257 mmoles of H_2O_2 ; H_2O_2 /benzene = 0.2) of an aqueous solution of H_2O_2 at 30% w/w are subsequently added over a period of 1 hour.

The reaction mixture is then cooled to 20°C and the catalyst is separated by filtration on a porous septum.

At the end of the reaction two phases are separated, with the following composition:

upper organic phase (42% by weight):

benzene/sulfolane/water 56/40/4 by weight

lower aqueous phase (58% by weight):

benzene/sulfolane/water 49/2/49 by weight.

The organic phase is analyzed by means of HPLC revealing the formation of the following products:

phenol 17.5 g (186.5 mmoles)

hydroquinone 1.23 g (11.14 mmoles)

catechol 1.84 g (16.72 mmol).

The reaction mixture was then evaporated at reduced pressure obtaining only traces of polyphenolic tars as boiler residue.

5 The reaction performances are consequently the following:

- benzene conversion (C1) = 16.7% (in moles);
- H₂O₂ conversion (C2) = 92% (in moles);
- selectivity to phenol (S1) = 87% (in moles);
- 10 - selectivity on H₂O₂ (S2) = 79% (in moles);
- concentration of phenol in the final reaction mixture (organic phase) = 7.28% (by weight).

Operating under these conditions, during the recovery and purification phase of the reaction products, it is
15 necessary to evaporate 12.7 Kg of solvent (sulfolane and non-reacted benzene) per Kg of phenol.

The co-production of by-products is equal to 69.9 kg hydroquinone/kg phenol and 104.9 kg catechol/ton phenol.

At the end of the separation procedure of the reaction
20 products, described in patent MI 2002A 001187, said by-products are obtained in aqueous solution. The solution, containing catechol (150 g/l) and hydroquinone (100 g/l) is then fed with a flow equal to 0.14 ml/min into a tubular reactor, made of AISI 316 steel, containing 5 g of Angel-
25 hard ESCATTM H-60 catalyst (Co/Mo/P), at a temperature of

450°C and a pressure of 25 bar, together with a stream of hydrogen which is such as to maintain a molar ratio hydrogen/(catechol + hydroquinone) equal to 20.5.

Operating under these conditions, a conversion of catechol and hydroquinone equal to 100% is obtained, with a production of 2.49 g (26.5 mmoles) corresponding to a transformation yield to phenol equal to 97%.

The overall selectivity of the process, calculated as total moles of phenol produced/moles of benzene converted x 100, proves to be equal to 99%.

EXAMPLE 4

The same procedure is adopted as described in Example 3, adding 21.8 g (384 mmoles of H_2O_2 ; H_2O_2 /benzene = 0.3) of an aqueous solution of H_2O_2 at 60% w/w.

The organic phase is analyzed by means of HPLC revealing the formation of the following products:

phenol	23.0 g (245.1 mmoles)
hydroquinone	2.70 g (24.51 mmoles)
catechol	4.04 g (36.77 mmoles)

The reaction mixture was then evaporated at reduced pressure obtaining only traces of polyphenolic tars as boiler residue.

The reaction performances are consequently the following:

- benzene conversion (C1) = 23.89% (in moles);

- H_2O_2 conversion (C2) = 98% (in moles);
- selectivity to phenol (S1) = 80% (in moles);
- selectivity on H_2O_2 (S2) = 65% (in moles);
- concentration of phenol in the final reaction mixture
5 (organic phase) = 9.85% (by weight).

Under these conditions, during the recovery and purification phase of the reaction products, it is necessary to evaporate 9.2 Kg of solvent (sulfolane and non-reacted benzene) per Kg of phenol.

10 The co-production of by-products is equal to 117.0 kg hydroquinone/kg phenol and 175.5 kg catechol/ton phenol.

Operating as described in Example 3, the by-products are subject to hydrogenation obtaining a conversion of catechol and hydroquinone equal to 100%, with a production
15 of 5.47 g (58.2 mmoles) corresponding to a transformation yield to phenol equal to 97%.

The overall selectivity of the process, calculated as total moles of phenol produced/moles of benzene converted x 100, proves to be equal to 99%.

20 EXAMPLE 5

The same procedure is adopted as described in Example 3, adding 29.1 g (513 mmoles of H_2O_2 ; $\text{H}_2\text{O}_2/\text{benzene} = 0.4$) of an aqueous solution of H_2O_2 at 60% w/w.

The organic phase is analyzed by means of HPLC revealing the formation of the following products:
25

phenol 27.4 g (291.63 mmoles)
hydroquinone 3.83 g (34.84 mmoles)
catechol 5.75 g (52.27 mmoles).

The reaction mixture was then evaporated at reduced
5 pressure obtaining only traces of polyphenolic tars as
boiler residue.

The reaction performances are consequently the follow-
ing:

- benzene conversion (C1) = 29.53% (in moles);
- 10 - H₂O₂ conversion (C2) = 98% (in moles);
- selectivity to phenol (S1) = 77% (in moles);
- selectivity on H₂O₂ (S2) = 58% (in moles);
- concentration of phenol in the final reaction mixture
(organic phase) = 11.73% (by weight).

15 Operating under these conditions, during the recovery
and purification phase of the reaction products, it is
necessary to evaporate 7.5 Kg of solvent (sulfolane and
non-reacted benzene) per Kg of phenol.

The co-production of by-products is equal to 139.8 kg
20 hydroquinone/kg phenol and 209.7 kg catechol/ton phenol.

Operating as described in Example 3, the by-products
are subject to hydrogenation obtaining a conversion of
catechol and hydroquinone equal to 100%, with a production
of 7.78 g (82.7 mmoles) corresponding to a transformation
25 yield to phenol equal to 97%.

The overall selectivity of the process, calculated as total moles of phenol produced/moles of benzene converted x 100, proves to be equal to 99%.

EXAMPLE 6

5 An AISI 316 reactor (volume = 600 ml) is pressurized with nitrogen to a pressure of 5 atm. 100 g of benzene (1.28 moles), 216 g of sulfolane, 85 g of water and 10 g of catalyst activated as specified in Example 1 (equal to 3.1 mmols of Ti) are then charged. The liquid fraction of the
10 reaction mixture is in this case three-phase. The temperature of the reactor is brought to 100°C.

29.1 g (257 mmols of H₂O₂; H₂O₂/benzene = 0.2) of an aqueous solution of H₂O₂ at 30% w/w are subsequently added over a period of 1 hour.

15 The reaction mixture is then cooled to 20°C and the catalyst is separated by filtration on a porous septum.

At the end of the reaction two phases are separated, with the following composition:

upper organic phase (43% by weight):

20 benzene/sulfolane/water 55/41/4 by weight

lower aqueous phase (57% by weight):

benzene/sulfolane/water 49/2/49 by weight.

The organic phase is analyzed by means of HPLC revealing the formation of the following products:

25 phenol 17.5 g (186.5 mmols)

hydroquinone 1.33 g (12.11 mmoles)
catechol 2.00 g (18.17 mmoles).

The reaction mixture was then evaporated at reduced pressure obtaining only traces of polyphenolic tars as
5 boiler residue.

The reaction performances are consequently the following:

- benzene conversion (C1) = 16.9% (in moles);
- H₂O₂ conversion (C2) = 98% (in moles);
- 10 - selectivity to phenol (S1) = 86% (in moles);
- selectivity on H₂O₂ (S2) = 74% (in moles);
- concentration of phenol in the final reaction mixture (organic phase) = 9.93% (by weight).

Operating under these conditions, during the recovery
15 and purification phase of the reaction products, it is necessary to evaporate 9.1 Kg of solvent (sulfolane and non-reacted benzene) per Kg of phenol.

The co-production of by-products is equal to 76.2 kg hydroquinone/kg phenol and 114.3 kg catechol/ton phenol.

20 Operating as described in Example 3, the by-products are subject to hydrogenation obtaining a conversion of catechol and hydroquinone equal to 100% is obtained, with a production of 2.70 g (28.8 mmoles) corresponding to a transformation yield to phenol equal to 97%.

25 The overall selectivity of the process, calculated as

total moles of phenol produced/moles of benzene converted x 100, proves to be equal to 99%.

EXAMPLE 7

The same procedure is adopted as described in Example 6, adding 21.8 g (384 mmols of H_2O_2 ; $\text{H}_2\text{O}_2/\text{benzene} = 0.3$) of an aqueous solution of H_2O_2 at 60% w/w.

The organic phase is analyzed by means of HPLC revealing the formation of the following products:

phenol	22.69 g (241.4 mmols)
10 hydroquinone	2.65 g (24.14 mmols)
catechol	3.98 g (36.20 mmols).

The reaction mixture was then evaporated at reduced pressure obtaining only traces of polyphenolic tars as boiler residue.

15 The reaction performances are consequently the following:

- benzene conversion (C1) = 23.5% (in moles);
- H_2O_2 conversion (C2) = 98% (in moles);
- selectivity to phenol (S1) = 80% (in moles);
- 20 - selectivity on H_2O_2 (S2) = 64% (in moles);
- concentration of phenol in the final reaction mixture (organic phase) = 13.41% (by weight).

Operating under these conditions, during the recovery and purification phase of the reaction products, it is 25 necessary to evaporate 6.5 Kg of solvent (sulfolane and non-reacted benzene) per Kg of phenol.

reacted benzene) per Kg of phenol.

The co-production of by-products is equal to 117.0 kg hydroquinone/kg phenol and 175.5 kg catechol/ton phenol.

Operating as described in Example 3, the by-products
5 are subject to hydrogenation obtaining a conversion of catechol and hydroquinone equal to 100%, with a production of 5.38 g (57.3 mmoles) corresponding to a transformation yield to phenol equal to 97%.

The overall selectivity of the process, calculated as
10 total moles of phenol produced/moles of benzene converted x 100, proves to be equal to 99%.

EXAMPLE 8

The same procedure is adopted as described in Example
6, adding 29.1 g (513 mmoles of H_2O_2 ; H_2O_2 /benzene = 0.4) of
15 an aqueous solution of H_2O_2 at 60% w/w.

The organic phase is analyzed by means of HPLC revealing the formation of the following products:

phenol	26.9 g (286.6 mmoles)
hydroquinone	3.98 g (36.20 mmoles)
20 catechol	5.97 g (54.30 mmoles).

The reaction mixture was then evaporated at reduced pressure obtaining only traces of polyphenolic tars as boiler residue.

The reaction performances are consequently the follow-
25 ing:

- benzene conversion (C1) = 29.4% (in moles);
 - H₂O₂ conversion (C2) = 98% (in moles);
 - selectivity to phenol (S1) = 76% (in moles);
 - selectivity on H₂O₂ (S2) = 57% (in moles);
- 5 - concentration of phenol in the final reaction mixture
 (organic phase) = 15.95% (by weight).

Operating under these conditions, during the recovery and purification phase of the reaction products, it is necessary to evaporate 5.3 Kg of solvent (sulfolane and non-
10 reacted benzene) per Kg of phenol.

The co-production of by-products is equal to 147.8 kg hydroquinone/kg phenol and 221.7 kg catechol/ton phenol.

Operating as described in Example 3, the by-products are subject to hydrogenation obtaining a conversion of
15 catechol and hydroquinone equal to 100%, with a production of 8.08 g (85.9 mmoles) corresponding to a transformation yield to phenol equal to 97%.

The overall selectivity of the process, calculated as total moles of phenol produced/moles of benzene converted x
20 100, proves to be equal to 99%.

CLAIMS

1. A process for the preparation of phenol comprising the following phases:

5 1) preparation in continuous of phenol by means of the direct oxidation of benzene with hydrogen peroxide operating with an H_2O_2 /benzene ratio ranging from 10 to 70%, in a three-phase reaction system comprising a first liquid phase consisting of benzene and an organic solvent, a second liquid phase consisting of water, a solid phase consisting of an
10 activated catalyst based on titanium silicalite TS-1;

2) separation of the phenol and non-reacted benzene from the reaction mixture of the oxidation section
15 (1), by means of fractionated distillation;

3) separation of the solvent and by-products consisting of benzenediols from the mixture coming from the distillation tail (2), by means of basic extraction;

20 4) transformation of the by-products obtained in section (3) to phenol by means of hydrodeoxygenation with hydrogen operating in continuous, in aqueous solution, at a temperature ranging from 250 to 500°C, at pressures of 1-100 bar and in the presence of a catalyst based on elements of group VIB
25

or their mixtures or group VIII of the periodic table or their mixtures;

5) recycling of the phenol obtained in section (4) to the distillation section (2).

- 5 2. The process according to claim 1, wherein the direct oxidation of benzene is carried out in a three-phase reaction system comprising a quantity of water ranging from 5 to 50% by weight with respect to the reaction mixture.
- 10 3. The process according to claim 2, wherein the water is present in a quantity ranging from 15 to 40%.
4. The process according to claim 1, wherein the direct oxidation of benzene is carried out in a three-phase reaction system comprising an organic solvent consisting of sulfolane, in quantities ranging from 20 to 80% by weight with respect to the reaction mixture.
- 15 5. The process according to claim 4, wherein the sulfolane is present in quantities ranging from 40 to 70%.
- 20 6. The process according to claim 1, wherein the direct oxidation of benzene with hydrogen peroxide is carried out in the presence of a catalyst based on titanium silicalite TS-1 selected from those having general formula (I);

25



wherein: x ranges from 0.0001 to 0.04, preferably from 0.02 to 0.03, in quantities ranging from 2 to 60% by weight with respect to the benzene, activated by means of a pretreatment with fluorine ions and hydrogen peroxide.

7. The process according to claim 6, wherein the catalyst is present in quantities ranging from 5 to 40% by weight with respect to the benzene.

8. The process according to claim 1, wherein the direct oxidation is carried out in quantities of benzene ranging from 10 to 80% by weight with respect to the reaction mixture.

9. The process according to claim 8, wherein the direct oxidation is carried out in quantities of benzene ranging from 15 to 50% by weight with respect to the reaction mixture.

10. The process according to claim 1, wherein the oxidation reaction is carried out at temperatures ranging from 50° to 110°C.

11. The process according to claim 10, wherein the oxidation reaction is carried out at temperatures ranging from 70° to 100°C.

12. The process according to claim 1, wherein the by-products consisting of benzenediols which are transformed into phenol are in aqueous solution at a con-

centration of 5-60% by weight.

13. The process according to claim 12, wherein the benzenediols are in aqueous solution at a concentration of 10-40% by weight.

5 14. The process according to claim 1, wherein the hydrodeoxygenation is effected with hydrogen operating with a molar ratio with respect to the benzenediols of 2-50.

15. The process according to claim 14, wherein a molar ratio of 5-30 is adopted with respect to the benzenediols.
10

16. The process according to claim 1, wherein the hydrodeoxygenation is carried out in the presence of a catalyst based on elements of group VIB and a promoter selected from elements belonging to group VIII and phosphorous.
15

17. The process according to claim 16, wherein the catalyst based on elements of group VIB is selected from molybdenum and tungsten and the promoter is selected from nickel, cobalt, iron and ruthenium.

20 18. The process according to claim 1, wherein the hydrodeoxygenation is carried out in the presence of a catalyst based on elements of group VIII selected from cobalt, palladium, nickel and platinum and a promoter selected from zinc, rhenium, selenium, tin, germanium
25 and lead.

19. The process according to claim 1, wherein the hydrodeoxygenation is carried out in the presence of a catalyst deposited on a carrier.
20. The process according to claim 19, wherein the carrier is selected from alumina, silica, titanium dioxide, crystalline or amorphous alumino-silicates, crystalline spinels having the general formula $F^{2+}R_2^{3+}O_4$, wherein F^{2+} is selected from Mg, Fe, Zn, Mn, Ni, and R^{3+} is selected from Al, Fe, Cr or their mixtures.
21. The process according to claim 16 and 19, wherein the hydrodeoxygenation is carried out in the presence of a catalyst based on an element of group VIB deposited on a carrier at a concentration ranging from 1 to 50% by weight and a promoter at a concentration ranging from 0.1 to 100% atomic with respect to the element of group VIB.
22. The process according to claim 18 and 19, wherein the hydrodeoxygenation is carried out in the presence of a catalyst based on an element of group VIII deposited on a carrier at a concentration ranging from 0.05 to 20% by weight and a promoter at a concentration ranging from 0.5 to 200% atomic with respect to the element of group VIII.

I, Antonella DE GREGORI of Via Borgonuovo 10, MILAN, Italy declare:

1. that I am well acquainted with the Italian and English languages;
2. that I am a sworn translator from and into the Italian and English languages;
3. that the translation contained therewith has been prepared by me and is a true translation from the Italian language of the document issued by the Italian Ministry of Industry, Trade and Handicraft – Italian Patent and Trademark Office – certifying the filing on the

28th day of NOVEMBER 2002 under No. MI2002 A 002522

by POLIMERI EUROPA S.p.A.

of an application for grant of a patent for industrial invention having the following title:

“INTEGRATED PROCESS FOR THE PREPARATION OF PHENOL FROM BENZENE WITH RECYCLING OF THE BY-PRODUCTS”


and of the specification and filing certificate attached thereto.

And I make this declaration conscientiously believing the same to be true.

Milan, this 28th day of SEPTEMBER 2005


(Antonella DE GREGORI)

Declared before me, in the city of Milan, Italy, by the aforesaid Antonella DE GREGORI
this 29th day of September 2005


(Notary Public)

